

# **SAFETY DATA SHEET**

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 453/2010

# 1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name NEOCOL B - BULK.

CAS No. Mixture.
EINECS No. Mixture.
REACH Registration No. None assigned.

1.2 Relevant identified uses of the substance or

mixture and uses advised against

Identified use(s)

A Black Magnetic Ink for use in the Magnetic Particle
Inspection Process (BS EN ISO 9934-2:2002).

Uses advised against None known.

1.3 Details of the supplier of the Safety Data

Sheet

Company Identification Johnson and Allen Ltd

Neocol Works Smithfield Sheffield S3 7AR. 0114 2738066.

Telephone 0114 2738066. Fax 0114 2729842.

E-Mail (competent person) info@johnsonandallen.co.uk

1.4 Emergency telephone number

Emergency Phone No. 0114 2738066. (UK office hours 08.30-17.00).

#### 2. SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

2.1.1 Regulation (EC) No. 1272/2008 (CLP) Asp. Tox. 1; May be fatal if swallowed and enters airways.

Repeated exposure may cause skin dryness or cracking.

2.1.2 Directive 67/548/EEC & Directive 1999/45/EC Xn; Harmful: may cause lung damage if swallowed.

Repeated exposure may cause skin dryness or cracking.

2.2 Label elements

Hazard Pictogram

2.2.1 Label elements According to Regulation (EC) No. 1272/2008 (CLP)

Product Name NEOCOL B – BULK.

GHS08

Signal word(s) Danger

Hazard statement(s) H304: May be fatal if swallowed and enters airways.

EUH066: Repeated exposure may cause skin dryness or

cracking.

Precautionary statement(s) P301 + P310: IF SWALLOWED: Immediately call a POISON

CENTRE or doctor/physician. P331: Do NOT induce vomiting.

P405: Store locked up.

P501: Dispose of contents/container to: Licensed recycler.

Revision: 4 Page: 1/7 Date: 19/04/2011



2.2.2 Label elements

According to Directive 67/548/EEC & Directive 1999/45/EC Hazard Symbol



Risk Phrases R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

S2, S23, S24, S62.

None.

**Additional Information** 2.4 For full text of H/P phrases see section 16.

# 3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Mixtures

2.3

EC Classification No. 1272/2008

Safety Phrases

Other hazards

Hazardous ingredient(s)	%W/W	CAS No.	EC No.	REACH Registration No.	Hazard pictogram(s) and Hazard statement(s)
Kerosene – unspecified – distillates (petroleum), hydrotreated light	>90	64742-47-8	265-149-8	01-2119453414- 43-0001	GHS08, Asp. Tox. 1; H304, EUH066.
Powder dispersion agent	<1	None assigned	None assigned	None assigned	None.

# FC Classification No. 67/548/FFC

Hazardous ingredient(s)	%W/W	CAS No.	EC No.	REACH Registration No.	EC Classification and Risk Phrases
Kerosene – unspecified – distillates (petroleum), hydrotreated light	>90	64742-47-8	265-149-8	01-2119453414- 43-0001	Xn; R65, R66.
Powder dispersion agent	<1	None assigned	None assigned	None assigned	None.

#### 3.2 Additional Information

For full text of H/P phrases see section 16.

#### **SECTION 4: FIRST AID MEASURES**



# Description of first aid measures

If breathing is difficult, remove victim to fresh air and keep at Inhalation

rest in a position comfortable for breathing. If symptoms

persist, obtain medical attention.

Skin Contact Wash with plenty of soap and water. Remove contaminated

clothing and wash clothing before reuse. If symptoms persist,

obtain medical attention.

Eye Contact Flush eyes with water for at least 15 minutes while holding eyelids open. If symptoms persist, obtain medical attention.

Ingestion IF SWALLOWED: Do NOT induce vomiting. Immediately call

Date: 19/04/2011 Revision: 4 Page: 2/7



a POISON CENTRE or doctor/physician.

4.2 Most important symptoms and effects, both acute and delayed

Aspiration into the lungs may cause chemical pneumonitis, which can be fatal. Repeated exposure may cause skin

dryness or cracking.

4.3 Indication of immediate medical attention and special treatment needed

Unlikely to be required but if necessary treat symptomatically.

# 5. SECTION 5: FIRE-FIGHTING MEASURES

5.1 **Extinguishing Media** 

> Suitable Extinguishing Media Extinguish with waterspray, foam or dry chemical. Unsuitable Extinguishing Media None known.

5.2 Special hazards arising from the substance or mixture

None known.

5.3 Advice for fire-fighters Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Avoild spraying water directly into storage containers due to danger of boilover.

#### 6. SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment Ensure adequate ventilation. Avoid inhalation of high

and emergency procedures concentrations of vapours. Wear suitable protective clothing,

gloves and eye/face protection.

**Environmental precautions** 6.2 Do not allow to enter drains, sewers or watercourses.

Methods and material for containment and Adsorb spillages onto sand, earth or any suitable adsorbent 6.3 cleaning up

material. Transfer to a container for disposal.

6.4 Reference to other sections See Also Section 8 and 13. 6.5

**Additional Information** None.

#### **SECTION 7: HANDLING AND STORAGE**

7.1 Precautions for safe handling Provide adequate ventilation. Avoid inhalation of high

> concentrations of vapours. Avoid prolonged skin contact. Wear suitable protective clothing, gloves and eye/face protection. Wash thoroughly with soap and water after handling. Do not eat, drink or smoke during work.

7.2 Conditions for safe storage, including any Store locked up.

incompatibilities

Storage Temperature

Ambient.

Storage Life Stable under normal conditions.

Incompatible materials Strong oxidising agents, Natural rubber, Polystyrene, Butyl

rubber.

7.3 A Black Magnetic Ink for use in the Magnetic Particle Specific end use(s) Inspection Process (BS EN ISO 9934-2:2002).

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

8.1 **Control parameters** 

8.1.1 **Occupational Exposure Limits** 

SUBSTANCE.	CAS No.	LTEL (8 hr	LTEL (8 hr	STEL	STEL	Note:
		TWA ppm)	TWA mg/m³)	(ppm)	(mg/m³)	
Kerosene – unspecified –	64742-47-8	150	1200	-	-	WEL (Reciprocal
distillates (petroleum),						Calculation
hydrotreated light						Method)

Revision: 4 Page: 3/7 Date: 19/04/2011



WEL: Workplace Exposure Limit (UK HSE EH40)

8.1.2 Biological limit value Not established.

8.1.3 PNECs and DNELs Not established.

8.2 Exposure controls

**8.2.1 Appropriate engineering controls** Provide adequate ventilation.

8.2.2 Personal protection equipment

Eye/face protection Wear protective eye glasses for protection against liquid

splashes.

Skin protection (Hand protection/ Other) Wear suitable gloves if prolonged skin contact is likely.

Impervious gloves (EN 374).

Respiratory protection Not normally required.

Handling of larger amounts: A suitable mask with filter type A

(EN14387 or EN405) may be appropriate. Use a

respirator/filter with at least: PF10: 10 x Protection Factor.

Not applicable.

**8.2.3 Environmental Exposure Controls**Do not allow to enter drains, sewers or watercourses.

# 9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

# 9.1 Information on basic physical and chemical

properties

Thermal hazards

Appearance Liquid.

Colour Dark grey/Black (Shaken).

Odour Paraffinic. Odour Threshold (ppm) Not available. Not applicable. pH (Value) Melting Point (°C) Not applicable. Boiling Point (°C) 235 - 270°C. >100°C. Flash Point (°C) Evaporation rate Not available. Non-flammable. Flammability Explosive limit ranges Not applicable. Vapour Pressure (mm Hg) Not available. Vapour Density (Air=1) Not available. Solubility (Water) Slightly soluble. Solubility (Other) Not available.

Partition Coefficient (n-Octanol/water)

Auto Ignition Temperature (°C)

Decomposition Temperature (°C)

Kinematic Viscosity

Explosive properties

Not available.

3.2cSt @ 40°C.

Not available.

Oxidising properties No information available.

**9.2 Other information** None.

Revision: 4 Page: 4/7 Date: 19/04/2011



#### 10. SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity
 10.2 Chemical stability
 10.3 Possibility of hazardous reactions
 10.4 Conditions to avoid
 10.5 Stable under normal conditions.
 10.6 Stable under normal conditions.
 10.7 Heat and direct sunlight.

10.5 Incompatible materials Strong oxidising agents, Natural rubber, Polystyrene, Butyl

rubber.

10.6 Hazardous Decomposition Product(s) None known.

#### 11. SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

11.1.1 Mixtures
Acute toxicity

Ingestion Low oral toxicity.

Kerosene – unspecified – distillates (petroleum), hydrotreated light: LD50 (rat): >15000mg/kg.

Inhalation Low acute toxicity.

Kerosene – unspecified – distillates (petroleum), hydrotreated light: LC50 (rat) 4hour(s): >4951mg/m³.

Skin Contact Low acute toxicity.

Kerosene – unspecified – distillates (petroleum), hydrotreated light: LD50 (rabbit): >2000mg/kg.

Eye Contact Low acute toxicity.

skin corrosion/irritation Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation Not classified.

Respiratory or skin sensitization Not expected to be a skin or respiratory sensitiser.

Repeated dose toxicity None anticipated.

**Carcinogenicity** No evidence of carcinogenicity.

**Mutagenicity** There is no evidence of mutagenic potential.

Reproductive toxicity None anticipated.

**Aspiration hazard** Asp. Tox. 1; May be fatal if swallowed and enters airways.

Aspiration into the lungs may cause chemical pneumonitis,

which can be fatal.

11.2 Other information None.

# 12. SECTION 12: ECOLOGICAL INFORMATION

**12.1 Toxicity** Low toxicity to aquatic organisms.

**12.2** Persistence and degradability The product is not biodegradable. There is evidence of

photodegradation in air. The product is unlikely to persist in

the environment.

**12.3** Bioaccumulative potential The product has potential for bioaccumulation.

Kerosene - unspecified - distillates (petroleum),

hydrotreated light: BCF = 130-159.

**12.4 Mobility in soil** Immiscible with water. The product is predicted to have low

mobility in soil. The product is volatile and will partition into the atmosphere. Higher molecular weight hydrocarbons: The substance may adsorb onto soils and sediments.

12.5 Results of PBT and VPVB assessment Not classified as PBT or vPvB.

12.6 Other adverse effects None.

# 13. SECTION 13: DISPOSAL CONSIDERATIONS

**13.1** Waste treatment methods

Dispose of contents/container to: Licensed recycler. Refer to manufacturer for information on recovery/recycling. Do NOT

Revision: 4 Page: 5/7 Date: 19/04/2011



landfill.

13.2 Additional Information Disposal should be in accordance with local, state or

national legislation.

# 14. SECTION 14: TRANSPORT INFORMATION

Not classified as dangerous for transport.

14.1	UN number	Not applicable.
14.2	Proper Shipping Name	Not applicable.
14.3	Transport hazard class(es)	Not applicable.
14.4	Packing Group	Not applicable.
14.5	Environmental hazards	Not applicable.
14.6	Special precautions for user	Not applicable.
14.7	Transport in bulk according to Annex II of	Not applicable.
	MARPOL73/78 and the IBC Code	
14.8	Additional Information	Not applicable.

#### 15. SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the

substance or mixture

15.1.1 EU regulations

Authorisations and/or restrictions on use None known.

Other EU regulations This product is not classified as a Volatile Organic

Compound according to the Directive 1999/13/EC.

15.1.2 National regulations None known.15.2 Chemical Safety Assessment Not available.

# **16. SECTION 16: OTHER INFORMATION**

The following sections contain revisions or new statements: 1-16.

#### **LEGEND**

LTEL Long Term Exposure Limit
STEL Short Term Exposure Limit
STOT Specific Target Organ Toxicity
DNEL Derived No Effect Level

PNEL Predicted No Effect Concentration

PBT PBT: Persistent, Bioaccumulative and Toxic vPvB vPvB: very Persistent and very Bioaccumulative

BCF Bioconcentration factor
Asp. Tox. 1 Aspiration hazard Category 1

Xn Harmful

#### **Risk Phrases and Safety Phrases**

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

S2 Keep out of the reach of children.

S23 Do not breathe vapour. S24 Avoid contact with skin.

S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

# Hazard statement(s)

H304 May be fatal if swallowed and enters airways.

EUH066 Repeated exposure may cause skin dryness or cracking.

Revision: 4 Page: 6/7 Date: 19/04/2011



Hazard pictogram(s) and Hazard Symbol

GHS08

Xn



Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Johnson and Allen Ltd gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Johnson and Allen Ltd accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Annex to the extended Safety Data Sheet (eSDS)

No information available.

Revision: 4 Page: 7/7 Date: 19/04/2011